

HIGHTEC FORMULA GT SAE 10W-40 HC

SHPD low viscosity engine oil based on HC synthetic base oils. Eminently suited to mixed vehicle fleets with petrol and diesel engines in passenger cars, heavy-goods vehicles, work machines and agricultural machinery.

Description

HIGHTEC FORMULA GT SAE 10W-40 HC is a Super High Performance Diesel (SHPD) engine oil produced using HC synthetic oils. Its high level of performance is achieved through the interaction of selected base oils and advanced additives.

Application

HIGHTEC FORMULA GT SAE 10W-40 HC is particularly suitable for vehicles equipped with Otto and diesel engines, with or without turbocharging. It is used in mixed vehicle fleets in engines from different manufacturers according to the manufacturer's specification. Its modern design makes a wide range of applications possible and ensures safe operation under all operating conditions.

Approvals

- Deutz DQC III-10
- Mack EO-N
- MAN M 3275-1
- MB-Freigabe 228.3/229.1
- MTU Type 2
- Renault RLD-2
- Volvo VDS-3

The quality of this product is equivalent to EU regulations

- ACEA E7
- ACEA A3/B4
- API SL/CI-4
- GLOBAL DHD-1
- JASO DH-1
- Allison C-4
- CAT ECF-2/ECF-1-a
- Cummins CES 20071/-72/-75/-76/-77/-78
- Detroit Diesel 93K215
- Fiat 9.55535-G2/D2
- Mack EO-M PLUS
- MB 235.27
- Voith Oil class A

Additionally this product is recommended when the following filling instructions are required

- Iveco 18-1804 T1/T2-E7

Benefits

- First-class economy grade for multi-functional use in different brands of diesel and Otto engines
- Suitable for both passenger cars and commercial vehicles, as well as agricultural and construction machinery
- It combines the specifications of European, American and Japanese manufacturers
- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Safer year-round operation due to outstanding viscosity-temperature behaviour and high shear stability
- Stable lubricating film, even with hot oil and under excessive loads
- Very low oil consumption
- High level of oxidation protection by means of selected HC synthetic oils and special additives
- Reliable protection against 'black sludge'
- Proper functioning of hydraulic tappets (hydraulic valve clearance compensation)
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full product benefits of HIGHTEC FORMULA GT SAE 10W-40 HC, a complete oil change is recommended.

Are you looking for the correct oil for your vehicle? Scan this code for the ROWE-oilfinder.



20003 | 17.08.2018

HIGHTEC FORMULA GT SAE 10W-40 HC

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,862
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	92,0
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,2
Viscosity index	ASTM D-7042	-	158
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	240
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-30
CCS	ASTM D-5293	cP @ °C	5600 @ -25
Total base number	DIN 51639-1	mgKOH/g	10,1
Acid number	-	mgKOH/g	< 1
HTHS	ASTM D4683	mPas	4,1
Sulphated ash	ASTM D874	wt-%	≤ 1,5

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe.com.de).

Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.



20003 | 17.08.2018