

HIGHTEC FORM SSU 9

Volatile, high-alloy punching and forming oil

Description

HIGHTEC FORM SSU 9 is a hydrocarbon-based metal forming lubricant free of aromatic compounds with a high level of performance. It does not have to comply with the 31 BimSchV (VOC-regulation) and does therefore not need to be included in the solvent balance.

Application

HIGHTEC FORM SSU 9 is applied undiluted onto the workpiece by either rolling or spraying. In many cases, the workpieces formed with HIGHTEC FORM SSU 9 are delivered to the subsequent processing steps without prior cleaning. A compatibility study is recommended in advance.

Benefits

- Outstanding performance in a variety of metal forming operations
- Wide field of application
- Toxicologically harmless
- Free of VOC
- Chlorine-free

Recommendation

Field of application:

- Pressing
- Punching
- Pipe bending
- Drawing

HIGHTEC FORM SSU 9 is suitable for machining materials made of steel, stainless steel and aluminium.

Notices

Storage:

When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 36 months
Temperature range: 0-40°C

Degreasing:

HIGHTEC FORM SSU 9 can be degreased with aqueous-alkaline cleaning agents and solvent cleaning agents in the event of planned cleaning of the workpieces.

Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.



60061 | 17.11.2015