

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

HIGHTEC ANTIFREEZE AN 12++

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Radiator anti-freeze

1.3. Details of the supplier of the safety data sheet

Company name:	ROWE MINERALOELWERK GMBH	
Street:	Langgewann 101	
Place:	D-67547 Worms	
Telephone:	+49 (0)6241 5906-0	Telefax: +49 (0)6241 5906-999
e-mail:	info@rowe-mineraloel.com	
Internet:	www.rowe-mineraloel.com	
Responsible Department:	Kundenservice	

1.4. Emergency telephone number: Giftnotruf Mainz (DE; E) +49 (0)6131-19240

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:


Harmful if swallowed.

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements
Regulation (EC) No. 1272/2008
Hazard components for labelling

ethanediol, ethylene glycol

Signal word: Warning

Pictograms:

Hazard statements

H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P330	Rinse mouth.
P501	Dispose of contents/container to of the disposal according to local regulations.

2.3. Other hazards

following inhalation: Vapour and mist concentrations above the allowable levels or unusually high concentrations may cause irritation to the nose and throat as well as headache, nausea and drowsiness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 2 of 8

After skin contact: Brief contact with the product may cause slight skin irritation. Prolonged contact (e.g. through soaked clothing) may result in serious skin irritation with symptoms such as redness and swelling.
 Following eye contact: Conjunctival redness.
 after ingestion: Oral ingestion of small amounts causes kidney damage.
 Caution if victim vomits: Risk of aspiration!

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
107-21-1	ethanediol, ethylene glycol			60 - <= 100 %
	203-473-3	603-027-00-1	01-2119456816-28	
	Acute Tox. 4, STOT RE 2; H302 H373			
107-21-1	ethanediol			15 - < 30 %
	203-473-3	603-027-00-1	01-2119456816-28	
	Acute Tox. 4, STOT RE 2; H302 H373			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Take off contaminated clothing.
 Self-protection of the first aider

After inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.
 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

After contact with skin

Wash with plenty of water. Change contaminated clothing. IF ON SKIN: Wash with plenty of water/?.
 If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist. Call a physician immediately.
 In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Medical treatment necessary. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.
 Rinse mouth immediately and drink plenty of water.
 Do NOT induce vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Ethylene glycol poisoning may cause initial symptoms such as behavioral disorders, drowsiness, vomiting, diarrhea, thirst and spasms. Kidney damage and kidney failure along with metabolic acidosis are late poisoning symptoms. Prompt medical treatment complemented by haemodialysis, if necessary, can reduce the toxic effect. Intravenous administration of ethanol in a sodium bicarbonate solution is a recognized antidote. For further treatment information, please consult the Poison Control Centre.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 3 of 8

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings. Dry extinguishing powder. Water fog. Foam. Carbon dioxide.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

The product itself does not burn. Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide carbon black Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. Do not breathe gas/fumes/vapour/spray. Special danger of slipping by leaking/spilling product. Ventilate affected area.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes. Wash hands thoroughly after handling. Protect skin by using skin protective cream.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Keep container in a well-ventilated place.

Hints on joint storage

Do not store together with: Oxidizing agents.

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 4 of 8

Do not store together with: Food and fodder

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink. Do not eat, drink, smoke or sneeze at the workplace. Keep away from food, drink and animal feedingstuffs. Protect skin by using skin protective cream. Wash hands before breaks and after work. Apply skin care products after work. Remove contaminated, saturated clothing immediately. Do not put any product-impregnated cleaning rags into your trouser pockets.

Eye/face protection

Wear eye/face protection.

Hand protection

Avoid contact with skin.

Tested protective gloves are to be worn: Butyl rubber. / NBR (Nitrile rubber).

Skin protection

Body protection: not required.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: magenta

pH-Value: 7,5-8,8 (33%)

Changes in the physical state

Initial boiling point and boiling range: not determined

Ignition temperature in °C:: >400 °C DIN 51794

Flash point: >100 °C DIN 51758

Lower explosion limits: not determined

Upper explosion limits: not determined

Test method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 5 of 8

Auto-ignition temperature

 Solid: No data available
 Gas: No data available

 Vapour pressure: <0,1 hPa
 (at 20 °C)

 Density (at 20 °C): ~1,126 g/cm³ DIN 51757

Water solubility: completely miscible

 Viscosity / kinematic: >22 mm²/s ISO 3219
 (at 20 °C)

9.2. Other information

Solid content: 0

pH pur (pH pure) ~8

SECTION 10: Stability and reactivity
10.3. Possibility of hazardous reactions

 possible with strong oxidizing agents.
 This product is stable under normal conditions. Hazardous reactions are unlikely.

10.5. Incompatible materials

Etchant and acids

10.6. Hazardous decomposition products

none

Further information

No thermal decomposition if properly stored / handled /transported.

SECTION 11: Toxicological information
11.1. Information on toxicological effects
Acute toxicity

Acute toxicity, dermal.

ATEmix calculated

ATE (oral) 532,4 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-21-1	ethanediol, ethylene glycol				
	oral	ATE 500 mg/kg			
	dermal	LD50 10600 mg/kg	Rabbit	GESTIS	
107-21-1	ethanediol				
	oral	ATE 500 mg/kg			
	dermal	LD50 10600 mg/kg	Rabbit	GESTIS	

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 6 of 8

Carcinogenic/mutagenic/toxic effects for reproduction

The product is not classified.

STOT-repeated exposure

Frequently or prolonged contact with skin may cause dermal irritation.

Specific effects in experiment on an animal

No data available

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC). Oral ingestion of small amounts causes kidney damage.

Contact with the eyes causes eye inflammation.

Inhalation of mists and vapours causes impaired consciousness.

Further information

No special hazards known when the product is properly used and the precautionary measures indicated are observed.

SECTION 12: Ecological information
12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
107-21-1	ethanediol, ethylene glycol					
	Acute fish toxicity	LC50 mg/l	18500	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 7500 mg/l	6500 -	96 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 10,000	48 h	Daphnia magna	
107-21-1	ethanediol					
	Acute fish toxicity	LC50 mg/l	18500	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 7500 mg/l	6500-	96 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	>10,000	48 h	Daphnia magna	

12.2. Persistence and degradability

According to EU criteria: expected to biodegrade fast The product basis (ethylene glycol) itself is readily biodegradable.

12.3. Bioaccumulative potential

No data available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-21-1	ethanediol, ethylene glycol	-1,34
107-21-1	ethanediol	-1,34

12.4. Mobility in soil

No data available.

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC). Do not allow uncontrolled discharge of product into the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 7 of 8

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

Waste disposal number of used product

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Contaminated packaging should be emptied to the maximum possible extent. After appropriate cleaning, it can be routed to reuse. Packaging not amenable to cleaning must be disposed of in accordance with the statutory regulations.

SECTION 14: Transport information
Land transport (ADR/RID)
Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)
Other applicable information (inland waterways transport)

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)
Other applicable information (marine transport)

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)
Other applicable information (air transport)

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information
Changes

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE AN 12++

Revision date: 10.01.2018

Product code: 21033-998-00

Page 8 of 8

This data sheet contains changes from the previous version in section(s): 1,2,3,4,8,11,15.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)